



Smaller. Slimmer. Lighter.

- 32% smaller redesigned Vertical Shock Rotator provides a slimmer profile
- 10.5% reduction in overall product weight reduces fatigue during activities
- 240% increase in vertical shock absorption reduces impact forces on the residual limb
- 88% more axial rotation reduces socket pressure while increasing comfort
- Extreme reliability for extended use in daily life and high impact activities
- Waterproof (fresh or saltwater)



L5987 + L5984

RUSH ROGUE® 2 TECHNICAL SPECS

iK3/4 **365 lbs**
▲ 165 kg

Item N°.		ROG2
Weight (26 Cat 4, with foot shell and spectra sock)		1039g
Build Height*	22 -24cm	6.125" / 155mm
	25 - 27cm	6.625" / 168mm
	28 - 29cm	6.750" / 171mm
Heel Height		3/8" / 10mm
Foot Shell		Light or Dark

*Build height based on size 23cm, 26cm, or 29cm Cat 4 foot module with Spectra sock, foot shell and 10mm heel height.



Module selection according to activity and weight									
Weight/ Activity level	0-105lbs 0-48kg	106-140lbs 49-64kg	141-175lbs 65-79kg	176-210lbs 80-95kg	211-245lbs 96-111kg	246-280lbs 112-127kg	281-315lbs 128-143kg	316-350lbs 144-159kg	351-365lbs 160-166kg
Low	1	2	3	4	5	6	7	8	9
Moderate	1	2	3	4	5	6	7	8	9
High	1	2	3	4	5	6	7	8	9
High impact	2	3	4	5	6	7	8	9	-

NOTE: Increasing category numbers indicate increased keel response. FOR BILATERAL PATIENTS: Increase by one category for added stability.



Available in EVAQ8 and H2O Models



Complete Prosthetic Foot Part Number (including foot shell)

Foot Module Part Number

	-		-		-	
Item No. ROG2 H2R2 EVQR2		Size 22-29cm		Category 1-9		Foot Shell Left Light: L1 Left Dark: L3 Right Light: R1 Right Dark: R3 H2O: X

