



Specifications

| | |
|-------------------------|------------------|
| SSK615 | |
| Weight Limit | 100 kg / 220 lb |
| Product Weight | 1100 g / 2.42 lb |
| Overall Height | 24 cm / 9.4 in |
| Distance to Knee Center | 3 cm / 1.2 in |
| Flexion | 145° |
| Warranty | 2 years |
| SSK615-THR | |
| Weight Limit | 125 kg / 275 lb |
| Product Weight | 1100 g / 2.5 lb |
| Overall Height | 23.2 cm / 9.1 in |
| Distance to Knee Center | 2 cm / 0.8 in |
| Flexion | 145° |
| Warranty | 2 years |

Select Stance Flexion Knee

- Polycentric, pneumatic 5-bar knee
- 9° of adjustable stance flexion
- Shock absorption at heel strike
- Independently adjustable pneumatic flexion and extension control
- Available with built-in proximal pyramid or threaded adapter
- Equipped with a built-in knee cap, preventing clothing from getting caught in the mechanism

Indications:

SSK615: Above knee amputation, medium to high impact level, K3-K4, maximum weight of 100 kg / 220 lb

SSK615-THR: Above knee amputation, medium to high impact level, K3-K4, maximum weight of 125 kg / 275 lb

Selection

| Model No. | Description | Weight Limit |
|------------|---|-----------------|
| SSK615 | Select Stance Flexion Knee with Proximal Pyramid | 100 kg / 220 lb |
| SSK615-THR | Select Stance Flexion Knee with Threaded Proximal Adapter | 125 kg / 275 lb |

Trulife Complementary Items

| | | | | | | | |
|---|--|--|--|---|-------------------------------------|---|---|
|  | AAASS237 3-Prong Rotatable Lamination Piece (page 26) |  | AAA214-01 Rotatable Female Insert (page 26) |  | STF190, 193 Triumph (page 13) |  | AAA135 Variable Height Adapter (page 28) |
|---|--|--|--|---|-------------------------------------|---|---|